

**CONFORM 4050RLA®****PAPER APPLICATION TAPE WITH RLA®**

4050RLA® Conform Series® application tape is standard weight saturated paper coated with a medium tack rubber adhesive designed specifically as a premasking of mid-sized die cut or prespaced vinyl and printed graphics. 4050RLA® features RLA® technology with improved adhesion to paper or film release liners.

**TECH DATA SHEET****PHYSICAL SPECIFICATIONS**

<b>Adhesive</b>	Rubber-based
<b>Color</b>	White/Translucent
<b>Caliper</b> <i>facestock</i>	100-113 microns (4.0 - 4.5 mils)
<b>Caliper</b> <i>facestock + adhesive</i>	125-138 microns (5.0 - 5.5 mils)
<b>Adhesion to Steel*</b>	13 - 15 N/100mm (12 - 14 oz.)
<b>Tensile</b>	297 N/100mm (17lb./in)
<b>Elongation</b>	3-4%
<b>Tear Resistance</b>	50
<b>Shelf Life**</b>	1 year

**FEATURES**

Removes easily following graphics application.  
 If adhesive touches adhesive, Conform pulls apart easily with no adhesive delamination.  
 Works well in either wet or dry applications with no adhesive transfer.

\* Adhesion PSTC-101, 1 min dwell on stainless steel

\*\* Stored at 22 OC / 50-55% RH



**RTape Corp.**  
 6 Ingersoll Road  
 South Plainfield, NJ  
 07080  
 T 1-800-440-1250  
[www.rtape.com](http://www.rtape.com)

**APPLICATIONS**

- Premask for small and medium size vinyl graphics.
- All-purpose application tape for wet and dry applications.
- Excellent for transferring graphics to banners.

**PRINTER PROFILES**

Printer profiles are available on [rtape.com](http://rtape.com).

**WARRANTY**

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.

RESPONSIVE  
 RELIABLE  
 RESOURCEFUL