



SOLVENT/ECO-SOLVENT/UV/LATEX PRINTING

RITMO 353SJ

Weight: 10.5 oz / 356 gsm

Thickness: 15 mil / 381 microns

Composition: 35% cotton, 65% polyester

Finish: Natural White / Semi-Matte

Roll Widths: 30"-126" (1.07m - 1.83m)



MANUFACTURED BY

ECKER TEXTILES, LLC

USA MADE 

FREDRIXPRINTCANVAS.COM

SINCE 1868

RITMO 353SJ

PRODUCT SPECIFICATION SHEET

INKJET PRINTING CANVASES

Style:	353SJ
Name:	RITMO
Item Master:	126XX
Composition:	35% cotton, 65% polyester
Weave Construction:	1:1
Coatings:	One Acrylic/Latex Primer Basecoat, Latex & Solvent Inkjet Printable Topcoat
Appearance:	Natural White
Texture:	Lightweight
Finish Weight (osy/gsm):	10.5 osy / 356 gsm
Thickness (mils/microns):	15 mil / 381 microns
Whiteness:	83.98
Brightness:	87.59
L:	95.72
a:	-0.28
b:	1.33
Gloss 60°:	4.0




MANUFACTURED BY


ECKER TEXTILES, LLC

This canvas is designed for digital printing applications using solvent based ink sets. Although designed for all printers using these ink sets, actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. The shelf life is 1 year at recommended temperature and humidity.

Ecker Textiles guarantees only the canvas itself against defects in quality or workmanship. No other warranty is expressed or implied.

VIII_XXVI_MMXXIV

 @FredrixPrintCanvas

 @FredrixPrintCanvas

 @FredrixPrint

 @Fredrix-Print-Canvas

INQUIRIES:

Phone:

1-770-557-3175 (USA)

1-770-557-3160 (INTL)

Fax: 1-770-963-1044

General Inquiries:

rluepke@eckertex.com

International Inquiries:

mmorel@eckertex.com

RITMO 353SJ